

Han Brid-Sti-c Abschlußstecker KuM20



| | |
|--------------------|---|
| Part number | 09 12 006 2691 |
| Specification | Han Brid-Sti-c Abschlußstecker KuM20 |
| HARTING eCatalogue | https://b2b.harting.com/09120062691 |

Identification

| | |
|----------------|----------------|
| Category | Inserts |
| Series | Han-Brid® |
| Identification | Han-Brid® Cu |
| Specification | Bus terminator |

Version

| | |
|---------------------|--|
| Gender | Male |
| Size | 3 A |
| Number of contacts | 2 |
| Additional contacts | + 4 electrical contacts 10 A + option for PE |

Technical characteristics

| | |
|-----------------------------------|-----------------------|
| Electrical data acc. to IEC 61984 | 10 A 50 V 0.8 kV 3 |
| Rated current | 10 A |
| Rated voltage | 50 V |
| Rated impulse voltage | 0.8 kV |
| Pollution degree | 3 |
| Insulation resistance | $\geq 10^{10} \Omega$ |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥ 500 |

Material properties

| | |
|---|--------------------------|
| Material (insert) | Polycarbonate |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material (hood/housing) | Polycarbonate |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |



Pushing Performance

Material properties

| | |
|-----------------------------|--|
| RoHS exemptions | 6c: Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|-----------------------|----------|
| Packaging size | 1 |
| Net weight | 34 g |
| Country of origin | Germany |
| Customs tariff number | 85366990 |