

Han 3EMC-HBM-SL



| | |
|--------------------|---|
| Part number | 09 62 003 0301 |
| Specification | Han 3EMC-HBM-SL |
| HARTING eCatalogue | https://b2b.harting.com/09620030301 |

Identification

| | |
|-----------------------------|---------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] EMC |
| Type of hood/housing | Bulkhead mounted housings |
| Description of hood/housing | Straight |

Version

| | |
|----------------------|--|
| Locking type | Single locking lever |
| Size | 3 A |
| Field of application | Hoods/Housings for higher EMC requirements |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP44 IP65 / IP67 with seal screw 09 20 000 9918 |

Material properties

| | |
|-----------------------------|--|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |
| Material (seal) | PTFE |
| Material (locking) | Steel |
| Surface (locking) | Zinc plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6a: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Pushing Performance

Material properties

| | |
|-----------------------|------|
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|-----------------------|----------|
| Packaging size | 10 |
| Net weight | 33.6 g |
| Country of origin | Germany |
| Customs tariff number | 85389099 |