Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: Böhmer-Leuchten						
Supplier's address: Böhmer-Leuchten, Lüttkewiesen 11, 59757 Müschede Arnsberg HSK, DE						
Model identifier: 34056						
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		matt cover				
(or other electric interface)						
Mains or non-m	nains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable	e light source:	Nein	Envelope:	-		
High luminance light source:		Nein				
Anti-glare shield:		Nein	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters: Energy consumption in on- 8 Energy efficiency F				F		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		٥	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		600 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	500	Spectral power	See image		
dimensions without	Width	40	distribution in the	in last page		
without	Depth	90		 		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	- -		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	80	Survival factor	0,95		
the lumen maintenance factor	0,95				

(a)'-': not applicable; (b)'-': not applicable;