## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trade mark:	ESYLUX					
Supplier's addre	ess: -						
Model identifie	r: EO10298950 A	A .					
Type of light so	urce:						
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS			
Light source cap-type		3 - 42 V DC, 449 mA CC					
(or other electric interface)  Mains or non-mains:		NMLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:		Nein	Envelope:	-			
High luminance light source:		Nein					
Anti-glare shield:		Nein	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		16	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P <sub>on</sub> ), expressed in W		16,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82			
Outer	Height	25	Spectral power	See image			
dimensions without	Width	240	distribution in the	in last page			
vviciiout	Depth	240					

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity	0,381			
			coordinates (x and y)	0,377			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		4	Survival factor	-			
the lumen maintenance factor		-					

(a)'-': not applicable; (b)'-': not applicable;

