Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Sun Cracks

Supplier's address: -

Model identifier: 100905

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Nicht					
(or other electric interface)	austauschbare Lichtquelle					
Mains or non-mains:	MLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:	Nein	Envelope:	-			
High luminance light source:	Nein					
Anti-glare shield:	Nein	Dimmable:	No			
Product parameters						

_		-				
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	20	Energy efficiency class	E		
Useful luminou indicating if it re in a sphere (36 cone (120º) or ir (90º)	efers to the flux 50°), in a wide	2 200 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode p expressed in W	ower (P _{on}),	20,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, expres rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	87		
Outer	Height	59	Spectral power	See image		
dimensions	Width	700	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	79	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	lf yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,380 0,378		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	33	Survival factor	-		
the lumen main	tenance factor	-				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,90	Colour consistency in McAdam ellipses	-		
Claims that source replaces light source with ballast of a parti Flicker metric (P	hout integrated cular wattage.	_(b) _	If yes then replacement claim (W) Stroboscopic effect	-		
		-	metric (SVM)	-		

(a)_{'-'} : not applicable;

(b)'-' : not applicable;