



Abbildung ähnlich

**Product Features**

Basic-line splice box, extensible, 19"/1U, 12xLC-D, OS2, blue

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit
- can be tilted downwards when opened
- front quick release (push-pull)
- 2 splice cassettes for holding 12 or 24 pigtails
- inserted crimp splice holder
- prepared with pigtails inserted in bundle of 12 incl. 12 x LC-D ceramic couplings
- 24 LC-fibre pigtails E9/125 µm, 2 m, SM PC, grade C
- with test protocol for all fibres incl. serial number
- 2 x PG13.5/M20 - cable glands in the back (each 2 x right/left)
- 1 x PG13.5 gland in scope of delivery
- black (similar to RAL 9005)

**Features**

| General                              |  |
|--------------------------------------|--|
| Surface                              | steel sheet, powder-coated   |
| Protection class IP                  | 20   |
| Halogen Free                         | Yes  |
| GTIN (EAN)                           | 4043921666982  |
| Mounting types                       |  |
| (19-inch)-installation, 1 rack unit  | Yes  |
| Dimensions/Weights without packaging |  |
| Length mm                            | 482  |
| Width mm                             | 245  |
| Height mm                            | 44   |
| Certifications                       |  |
| RoHS conform                         | Yes  |
| References                           |  |
| Accessories                          | 228040002, 228040102, 228040302, 228060000, 228060100, 228060300, 228070000, 228070100, 228070200, 228070312 |