Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC

Supplier's address: Einkauf, Gewerbestraße 10, DE

Model identifier: LED15MG4LKW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G4		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consump mode (kWh/1000 up to the nearest) h), rounded	3	Energy efficiency class	E		
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	ers to the flux)º), in a wide	275 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode po expressed in W	wer (P _{on}),	2,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	36	Spectral power	See image		
dimensions	Width	36	distribution in the	in last page		

Claim of equivalent power ^(a) - If yes, equivalent power (W) - Chromaticity 0,312 coordinates (x and y) 0,337	without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	10	range 250 nm to 800 nm, at full-load	
	Claim of equival	lent power ^(a)	-	, , ,	-
coordinates (x and y) 0,337				Chromaticity	0,312
				coordinates (x and y)	0,337
Parameters for LED and OLED light sources:					
R9 colour rendering index value5Survival factor0,90	R9 colour render	ring index value	5	Survival factor	0,90
the lumen maintenance factor 0,70	the lumen maint	tenance factor	0,70		

(a)'-' : not applicable;

(b)'-' : not applicable;

