## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	trade mark:	SPL
--------------------	-------------	-----

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L641801030-1

Τv	pe	of	light	soui	ce:
. ,	P-	•			···

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	R7s		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## **Product parameters**

Parameter		Value	Parameter	Value
		General product p	arameters:	
٠,	nption in on- 00 h), rounded st integer	10	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	10,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, lighting control	Height	20	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image
	Width	118		in last page
	Depth	20		

parts and non- lighting con- trol parts, if				
any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,436	
		nates (x and y)	0,397	
Parameters for LED and OLED lig	tht sources:	'		
R9 colour rendering index value	10	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;

